



Dunbrik (Yorks) Ltd.

172, Ferry Lane, Stanley Wakefield, WF3 4LT tel: 01924 373694 fax: 01924 383459

email: flues@dunbrik.co.uk web: www.dunbrik.co.uk

Declaration of Performance Ref. 0086-CPD-597465

Product Dunbrik A1 Concrete Flue Liners

Designation T600 N1 D 3 G

Intended Use For domestic chimneys.

Jointed with Dunseal universal fireproof mortar paste

For conveying products of combustion from heating appliances to the

outside atmosphere

Manufacturer Dunbrik (Yorks) Limited

172 Ferry Lane, Stanley, Wakefield WF3 4LT, UK

In compliance with EU Construction Products Directive - 89/106/EEC

Performance assessment procedure System 2+

Harmonised standard EN 1857:2010

Chimneys - Components - Concrete flue liners

Notified Body for the above Directive BSI Assurance UK Ltd - Notified Body No. 0086

Factory production control Certificate 0086-CPD-597465 24th June 2013

Declared performance:

Essential characteristics	Performance Round liners	Performance Square liners
Compressive strength		
(declared structural height)	18.1m	20m
Reaction to fire	A1	A1
Flow resistance: Mean roughness	Pass	Pass
Thermal resistance	2.27 /m ² K/W	0.120 / m ² K/W
Durability: Abrasion	0.03Kg/m ²	0.03Kg/m ²
Freeze/thaw resistance:	N.P.D.	N.P.D.
Release of dangerous substances:	none	none

The performance of the above products is in conformity with these declared performances. This declaration of performance is issued under the sole responsibility of Dunbrik (Yorks) Ltd.

Signed for and on behalf of Dunbrik (Yorks) Ltd

Daniel Shute Director

Issued 28th June 2013



